

KIR-R20



Features

Weatherproof IR Camera

SONY/SHARP Color CCD

IR LED: ϕ 5X23PCS ,IR Distance:20M

Water Resistance : IP66

3 Axis Bracket

Auto White Balance(AWB)

Lens: Board Lens 3.6mm/F2.0

Dimension : 126(W) x 69(H) x67(D)mm



Specifications

Model	KIR-601R20	KIR-821R20
Image Sensor	1/3"SONY	1/4"SHARP
Horizontal Resolution	420 TV Line	420 TV Line
Pixels	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
TV System	PAL/NTSC	
IR LED	ϕ 5 X 24 PCS	
IR Series Distance	20 M	
Lens	Board Lens 3.6mm/F2.0	
Sync System	Internal	
IR Status	Under 10 Lux By CDS	
Usable Illumination	0 Lux/F2.0 (LED ON)	
IR Power On	CDS Auto Control	
S/N Ratio	\geq 48dB (AGC OFF)	
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75 Ω)	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max	
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max	
White Balance	Auto	
Power Source	DC12V 300mA	
Dimension	126(W) x 69(H) x67(D)mm	
Weight	700g	